

## DATA LOGGERS FOR TEMPERATURE AND HUMIDITY (BASIC TYPE)

DATA  
OUTPUT

- Built-in high-precision sensor
- 260,000 memory for long-term logging
- Unit: °C/°F
- Temperature and humidity upper and lower limit alarm
- Temperature and humidity linear correction function
- Battery level display
- Computer software is included



0318-TH26B

### STANDARD DELIVERY

Main unit	1 pc
Software and USB cable	1 pc
4G USB flash disk	1 pc

### SPECIFICATION

Code	0318-TH26A	0318-TH26B
Temperature range	-20°C~60°C/-4°F~140°F	
Temperature accuracy	±0.5°C (at 0°C~60°C), other range ±0.8°C ±0.9°F (at 32°F~140°F), other range ±1.4°F	±0.3°C/±0.6°F
Temperature resolution	0.1°C/0.1°F	
Humidity range	0%RH~100%RH	
Humidity accuracy	±5%RH (at 10%RH~90%RH), other range ±7%RH	±3%RH
Humidity resolution	0.1%RH	
Memory size	260,000	
Sampling interval	2s~255s (adjustable)	
Logging interval	5s~18h (adjustable)	
Logging start mode	key operation/time-lapse start/timing start	
Logging end mode	key operation/Full/timing end	
Interface	Micro USB	
Power supply	3.7V rechargeable lithium battery, working time: 1 year (with logging interval of 10min) 5V DC	
Dimension (W×D×H)	120×33×113mm	
Weight	209g	

software (included), download data to PC software via USB cable and save the data as XLS, TXT, PDF format (cannot display data in real time)

