


MULTI-FUNCTION SCALES

- Zero-setting, weighing, subtracting tare value
- Counting, accumulation, percentage display, checking alarm
- Built-in calibration weights, automatic internal calibration
- 7-inch resistive touch color screen
- With a hook at the bottom
- Unit: g, ct, GSM, oz, kg, lb, mg
- 304 stainless steel weighing pan
- Overload alarm
- Data output



Unit: mm

INTERNAL CALIBRATION

TOUCH SCREEN

DATA OUTPUT

Calibration methods:



Internal calibration



Linear calibration



Fixed value calibration

Measurement functions:



Weighing



Checking alarm



Percentage



Counting



Density (applicable for measuring solid density with $\rho > 1\text{g/cm}^3$, density accessories are not included)



8006-10



printer (optional)



GSM cutter (optional)



scanner (optional)



hydrostatic stand (optional,
for 8006-5, 8006-10,
8006-5A, 8006-10A)

SPECIFICATION

Operation temperature	15~30°C
Operation humidity	≤85%RH
Weighing pan size	305×230mm
Power supply	rechargeable lead acid battery (9V/3Ah)
Stable reading time	≤2s
Output	RS232, USB (data export, unable to communicate)

OPTIONAL ACCESSORY

RS232 cable*	8306-CABLE*
Printer	8306-PRINTER
Hydrostatic stand	8006-HWS
Scanner	8006-SCAN (RS232 port)
GSM cutter	8390-100

* Used to connect to computers

Code	Maximum weighing	Resolution (d)	Minimum weighing	Accuracy (m is load)	Linearity	Repeatability	Verification interval (e)
8006-5	5kg	1g	20g	±5g	±5g	±3g	10g
8006-10	10kg	1g	20g	m≤5kg: ±5g; m>5kg: ±10g	±5g	±3g	10g
8006-20	20kg	1g	20g	m≤5kg: ±5g; m>5kg: ±10g	±5g	±4g	10g
8006-30	30kg	1g	20g	m≤5kg: ±5g; 5kg<m≤20kg: ±10g; m>20kg: ±15g	±5g	±4g	10g
8006-5A	5kg	0.1g	5g	±0.5g	±0.5g	±0.3g	1g
8006-10A	10kg	0.1g	5g	m≤5kg: ±0.5g; m>5kg: ±1g	±0.5g	±0.3g	1g
8006-20A	20kg	0.1g	5g	m≤5kg: ±0.5g; m>5kg: ±1g	±0.5g	±0.4g	1g
8006-30A	30kg	0.1g	5g	m≤5kg: ±0.5g; 5kg<m≤20kg: ±1g; m>20kg: ±1.5g	±0.5g	±0.5g	1g