


SALT SPRAY TEST CHAMBER

CUSTOMISABLE STUDIO SIZE

COMPLY WITH ISO STANDARD SALT SPRAY TEST REQUIREMENT



SFT-T350



- Adopting plastic precision nozzle and cone spraying device, even mist falling, fast, Long nozzle life, no crystallisation
- Spraying time can be controlled internally without the need for an external time relay
- Adjustment of brine flow and compressed air pressure by means of a flow meter and a high-pressure valve to ensure uniform salt spray deposition
- Adopt manual water filling system, water level is insufficient to automatically replenish the function, to ensure that the test is not interrupted
- USB port for download curves and historical data

SPECIFICATION

Advanced type	Code	SFT-T350	SFT-U680	SFT-E305	SFT-S410
	test condition	Suitable for NSS (Neutral), AASS (Acid), CASS (Copper Accelerated) test			
Basic type	Code	SFT-S210R	SFT-G550	SFT-L965	SFT-V125
	test condition	NSS (Neutral), AASS (Acid) test only			
Work chamber dimension (W×H×D)	900x600x500mm	1200x850x500mm	1600x850x550mm	2000x950x600mm	
Work chamber volume	270L	480L	740L	1440L	
Saline tank volume	25L	90L	90L	120L	
Work chamber temperature	(NSS, AASS)Test temperature: 35°C±1°C/ (CASS)Test temperature: 50°C±1°C				
Saturated barrel temperature	(NSS, AASS)Test temperature: 47°C±1°C/ (CASS)Test temperature: 63°C±1°C				
Saline temperature	(NSS, AASS)Test temperature: 35°C±1°C/ (CASS)Test temperature: 50°C±1°C				
Heat type	Advanced type: thermal radiation heat/Basic type: steam heat				
Test fluid	NSS: pure water+NaCl (pH 6.5~7.2), AASS: pure water+NaCl+CH ₃ COOH (pH 3.0~3.3) CASS: pure water+NaCl+CuCl ₂ (pH 3.0~3.3)				
Compressed air pressure	0.2MPa	0.6MPa	0.6MPa	0.6MPa	
Power	2kW	3kW	4kW	4.5kW	
Electricity supply	AC 220V, 1Ø, 50HZ				
External dimension (W×H×D)	1460x910x500mm	1900x1150x1500mm	2300x1150x1550mm	2700x1350x1600mm	
Weight (basic type)	108kg	485kg	585kg	760kg	
Weight (advanced type)	105kg	385kg	480kg	580kg	

STANDARD DELIVERY

Main unit	1pc
Sample holder	1group
Sodium chloride NaCl	2bottles
10L salt water preparation cup	1pc
80cm ² collection cup	2pcs
50cm glass measure cylinder	2pcs

OPTIONAL DELIVERY

Nozzle	SFT-S210R-NOZZLE
Brine Filter	SFT-S210R-FILTER