

三針

- 量針長度L=45mm
- 材質: 硬質合金(0.3mm以下為軸承鋼)
- 硬度HRA90
- 直徑精度: $\pm 0.5\mu\text{m}$
- 圓度: $0.5\mu\text{m}$
- 帶生產廠檢驗證書

型號	量針直徑($\varnothing d$)	適用的螺距
7394-60A*	0.170mm	0.2mm, 0.25mm, 0.3mm
7394-61A*	0.195mm	0.35mm
7394-62A*	0.220mm	0.4mm
7394-63A*	0.250mm	0.45mm
7394-64A*	0.290mm	0.5mm
7394-65A	0.335mm	0.6mm
7394-66A	0.390mm	0.7mm
7394-67A	0.455mm	0.75mm, 0.8mm
7394-68A	0.530mm	0.9mm

*材質為軸承鋼



可定制量針直徑 $\varnothing d$

型號	量針直徑($\varnothing d$)	適用的螺距
7394-69A	0.620mm	1.0mm
7394-70A	0.725mm	1.25mm
7394-71A	0.895mm	1.5mm
7394-72A	1.100mm	1.75mm, 2.0mm
7394-73A	1.350mm	2.5mm
7394-74A	1.650mm	3.0mm
7394-75A	2.050mm	3.5mm
7394-76A	2.550mm	4mm, 4.5mm
7394-77A	3.200mm	5mm, 5.5mm, 6mm



7394-76A

