

- 觸摸LCD顯示屏
- 測試完成后取下試樣, 使用顯微鏡測量壓痕直徑, 輸入壓痕直徑后自動計算硬度值
- 電動加載試驗力, 無砝碼
- 鑄造機殼, 結構穩定不變形
- 符合ISO 6506標準



技術參數

型號	HDT-MBE320-U	
布氏試驗力	62.5kgf, 100kgf, 125kgf, 187.5kgf, 250kgf 500kgf, 750kgf, 1000kgf, 1500kgf, 3000kgf	
布氏標尺	HBW2.5/62.5, HBW2.5/187.5, HBW5/62.5, HBW5/125, HBW5/250, HBW5/750, HBW10/100, HBW10/250, HBW10/500, HBW10/1000, HBW10/1500, HBW10/3000	
測定範圍	10~650HBW	
硬度測量解析度	0.1HBW	
工作臺升降	手動	
載荷控制	自動(加荷/保荷/卸荷)	
保荷時間	5~60秒	
測量顯微鏡	倍率	20X
	解析度	0.01mm
最大試樣高度	230mm	
壓頭中心至機身距離	140mm	
電源	AC110V, 60HZ, 1Ø	
尺寸	550×210×750mm	
重量	130kg	



標準配置

主機	1個
Ø78mm平臺	1個
Ø200mm平臺	1個
V形臺	1個
Ø2.5mm布氏壓頭	1個
Ø5mm布氏壓頭	1個
Ø10mm布氏壓頭	1個
硬度塊100~200HBW2.5/187.5	1個
硬度塊90~200HBW10/1000	1個
硬度塊100~200HBW10/3000	1個
測量顯微鏡	1個

可選配件

硬度塊100~200HBW2.5/187.5	HDT-B-HB25A1
硬度塊90~200HBW10/1000	HDT-B-HB10C1
硬度塊100~200HBW10/3000	HDT-B-HB10A1
硬度試驗機工作臺	HDT-DESK