

ZOOM STEREO MICROSCOPE (PROFESSIONAL TYPE) CODE 5107-S70T



LED ring light (optional)



- Greenough optical system, clear observation, real color
- High working distance is convenient for operation
- Excellent flat image and large depth of field, make observation comfortable
- 6.7:1 large zoom ratio, allow quick observation adjustment

SPECIFICATION

| | |
|-------------------------------|--------------------------------------------------------------|
| Optical tube | trinocular |
| Eyepiece (wide field) | 10X (view field: Ø22mm) |
| Objective | 0.67X~4.5X (zoom) |
| Observation tube | 45° trinocular tube inclination angle, built-in 0.5X adapter |
| Zoom ratio | 6.7:1 |
| Pupil distance | 50~75mm |
| Diopter adjustment | -8~+5 diopter (both eyepieces) |
| Working distance of objective | 110mm |
| Max. workpiece height | 106mm |
| Illumination | adjustable LED light |
| Power supply | 110/220V |
| Dimension (L×W×H) | 330×300×368mm |
| Weight | 3.5kg |



frosted glass filter (included)



white/black plate (included)

STANDARD DELIVERY

| | |
|--------------------------|-------|
| Main unit | 1 pc |
| 10X eyepiece | 2 pcs |
| Ø100mm glass plate | 1 pc |
| Ø100mm white/black plate | 1 pc |
| Anti-dust cover | 1 pc |

OPTIONAL ACCESSORY

| | | |
|---------------------|---------------------------|--------------------------------|
| Auxiliary objective | 0.5X | 5107-S70T-OB05X |
| | 1.5X | 5107-S70T-OB15X |
| | 2X | 5107-S70T-OB20X |
| Eyepiece | 15X (view field: Ø16mm) | 5107-S70T-EP15X |
| | 20X (view field: Ø12.5mm) | 5107-S70T-EP20X |
| LED ring light | | ISM-ZS-RL |
| Digital camera | | ISM-CM20, ISM-CM63, ISM-ZS70-S |