




ISV-S106

SPECIFICATION

Code		ISV-T105	ISV-S106	
	diameter (ØD)	6mm		
Lens	pixel	1M		
	resolution	1280×720		
	depth of field	20~150mm		
	bending direction	360°		
	bending range (α)	0°~220°		
	angle of view (θ)	120°		
	illumination	7 pcs LED, with 6 levels control		
	illuminance	25000 Lux		
	lens	sapphire glass lens		
	dust/waterproof	IP67		
	bend control	manual joystick		
	temperature alarm	temperature sensor (optional)		
Cable	length	1m	1.5m	
Cable	type	tungsten wire weaved cable		
	display	3.5" IPS full-view display		
	display resolution	640×480		
	function	take pictures, take videos		
	file format	picture: JPG, video: MP4		
Main unit	image process	image zoom (1X, 2X, 3X, 4X, 5X)		
Main unit	memory	memory card (Maximum: 64G)		
	output	USB, HDMI, WIFI (optional)		
	dust/waterproof	IP65		
	power supply	rechargeable lithium battery (working time ≥ 3 hours; optional: additional battery, working time ≥ 9 hours) AC/DC adapter (for continuous working)		
Weight		1000g		



220° bending angle



120° view angle



LED 6 levels control



360° bending direction

STANDARD DELIVERY

Main unit (with cable & lens)	1 pc
16G SD card	1 pc
Card reader	1 pc
USB cable	1 pc
Battery	1 pc
AC/DC adapter	1 pc

OPTIONAL ACCESSORY

Additional battery	ISV-S106-BATTERY (must be installed in factory)
WIFI output	ISV-S106-WIFI
Temperature alarm	ISV-S106-HT-ALARM