



## 直進式螺紋外徑測微器

- 用于測量螺紋中徑
- 解析度: 0.01mm
- 直進式, 測頭不旋轉
- 棘輪測力
- 配60°標準杆(除0-25mm外)
- 可選附件: 55°標準杆, 測頭(7381系列)




**3281-25A**  
(測頭選配)



安裝測頭后精度

測頭不旋轉



(mm)

型號	測定範圍	L	b	55°標準杆(選配)
<b>3281-25A</b>	0-25mm	42mm	26mm	—
<b>3281-50A</b>	25-50mm	67mm	38mm	<b>3281-SP1</b>
<b>3281-75A</b>	50-75mm	92mm	50mm	<b>3281-SP2</b>
<b>3281-100A</b>	75-100mm	117.6mm	62mm	<b>3281-SP3</b>
<b>3281-125A</b>	100-125mm	143mm	70mm	<b>3281-SP4</b>
<b>3281-150A</b>	125-150mm	168.2mm	82mm	<b>3281-SP5</b>

螺距	測定範圍							
	0-25	25-50	50-75	75-100	100-125	125-200	200-225	225-300
<b>0.4~0.5</b>	±0.01	—	—	—	—	—	—	—
<b>0.6~0.8</b>	±0.01	±0.013	—	—	—	—	—	—
<b>1~1.25</b>	±0.012	±0.015	±0.017	±0.017	—	—	—	—
<b>1.5~2.0</b>	±0.014	±0.017	±0.019	±0.019	±0.020	±0.023	±0.025	±0.028
<b>2.5~3.5</b>	±0.016	±0.019	±0.021	±0.021	±0.023	±0.025	±0.028	±0.031
<b>4.0~7.0</b>	—	±0.021	±0.023	±0.023	±0.025	±0.028	±0.031	±0.033