



4130-10



- 符合ISO 1502
- 包含通規和止規
- 帶生產廠檢驗證書

\* 型號說明舉例:

公稱直徑	螺距	等級6H
M0.8	0.2	-D8

型號為4130-D8

## 單支

規格(mm)		型號(4130) <sup>*</sup>		
公稱直徑	螺距	等級6H	等級6G	等級4H
M0.8	0.2	-D8	-D8G	-
M0.9	0.225	-D9	-	-
M1	0.25	-1	-	-1H
M1.2	0.25	-1D2	-1D2G	-1D2H
M1.4	0.3	-1D4	-	-1D4H
M1.6	0.35	-1D6	-1D6G	-1D6H
M1.7	0.35	-1D7	-	-
M1.8	0.35	-1D8	-1D8G	-1D8H
M2	0.4	-2	-2G	-2H
M2.2	0.45	-2D2	-2D2G	-2D2H
M2.3	0.4	-2D3	-2D3G	-
M2.5	0.45	-2D5	-2D5G	-2D5H
M2.6	0.45	-2D6	-2D6G	-
M3	0.5	-3	-3G	-3H
M3.5	0.6	-3D5	-3D5G	-3D5H
M4	0.7	-4	-4G	-4H
M4.5	0.75	-4D5	-4D5G	-4D5H
M5	0.8	-5	-5G	-5H
M6	1	-6	-6G	-6H
M7	1	-7	-7G	-7H
M8	1.25	-8	-8G	-8H
M9	1.25	-9	-9G	-9H
M10	1.5	-10	-10G	-10H
M11	1.5	-11	-11G	-11H
M12	1.75	-12	-12G	-12H
M14	2	-14	-14G	-14H
M16	2	-16	-16G	-16H
M18	2.5	-18	-18G	-18H
M20	2.5	-20	-20G	-20H
M22	2.5	-22	-22G	-
M24	3	-24	-24G	-
M27	3	-27	-27G	-
M30	3.5	-30	-30G	-
M33	3.5	-33	-33G	-
M36	4	-36	-36G	-36H
M39	4	-39	-39G	-
M42	4.5	-42	-	-
M45	4.5	-45	-	-
M48	5	-48	-	-
M52	5	-52	-52G	-
M56	5.5	-56	-	-
M60	5.5	-60	-	-

## 套裝(6H)

型號	包含的栓規(mm)
4130-S7	M3×0.5(4130-3), M4×0.7(4130-4), M5×0.8(4130-5), M6×1(4130-6), M8×1.25(4130-8), M10×1.5(4130-10), M12×1.75(4130-12)