

三針




- 與標準外徑測微器配合測量螺紋中徑
- 直徑精度: $\pm 0.5\mu\text{m}$
- 圓柱度: $1\mu\text{m}$
- 硬度: HRC60
- 帶生產廠檢驗證書

應用于測杆直徑**6.50mm(ØD)**的外徑測微器

型號	量針直徑	適用的螺距
7382-21	Ø0.170mm	0.2mm, 0.25mm, 0.3mm
7382-22	Ø0.195mm	0.35mm
7382-23	Ø0.220mm	0.4mm
7382-24	Ø0.250mm	0.45mm
7382-25	Ø0.290mm	0.5mm
7382-26	Ø0.335mm	0.6mm
7382-27	Ø0.390mm	0.7mm
7382-28	Ø0.455mm	0.75mm, 0.8mm
7382-29	Ø0.530mm	0.9mm
7382-210	Ø0.620mm	1.0mm



視頻



應用于測杆直徑**6.50mm(ØD)**的外徑測微器

型號	量針直徑	適用的螺距
7382-211	Ø0.725mm	1.25mm
7382-212	Ø0.895mm	1.5mm
7382-213	Ø1.100mm	1.75mm, 2.0mm
7382-214	Ø1.350mm	2.5mm
7382-215	Ø1.650mm	3.0mm
7382-216	Ø2.050mm	3.5mm
7382-217	Ø2.550mm	4mm, 4.5mm
7382-218	Ø3.200mm	5mm, 5.5mm, 6mm
7382-2S	18對/套, 包含以上所有3針	



7382-29

應用

